

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 63-039482

(43)Date of publication of application : 19.02.1988

(51)Int.Cl.

H02P 3/12

H02P 7/288

(21)Application number : 61-183587

(71)Applicant : TOKYO ELECTRIC CO LTD

(22)Date of filing : 05.08.1986


(72)Inventor : ITO NAOKI

## (54) DRIVE CIRCUIT FOR DC MOTOR

## (57)Abstract:

PURPOSE: To simplify circuit constitution, and to improve the safety of the whole motor drive circuit by forming a brake current circuit by a diode and a control transistor.

CONSTITUTION: When a motor-ON signal reaches an L level, a switching transistor 22 is conducted, and a DC motor 23 is turned. When the motor-ON signal is changed into an H level from the L level, the transistor 22 is interrupted, and the supply of DC currents to the DC motor 23 is stopped. A diode 27 is brought to a forward bias state by induced voltage generated by revolution by the inertia of the DC motor 23. Accordingly, a brake DC circuit for the DC motor 23 is formed by the diode 27 and a control transistor 25, and the DC motor 23 is brought to a braking state.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office